

AJAX Tools



“MAXIMUS”

PILOTED CARBIDE ROCK BITS

USED IN CONCRETE AND ROCK FOR DRILLING AND ANCHORING



Pat. No. 10,385,620

Pilot starts hole faster and more accurately, while removing initial material allowing outer carbides to drill hole with less drag.

**FITS “H” THREADED DRILL RODS
AVAILABLE IN 1-3/8” TO 3” DIAMETERS**



MAXIMUS VS STANDARD BIT



**30%
FASTER
DRILLING**

**ACCURATE
DRILLING**



DRILLS ACCURATE HOLE LOCATION



Ajax Tool Works, Inc.

10801 Franklin Ave. Franklin Park, IL 60131 • toll free: 800-323-9129 toll free fax: 800-424-2529
www.ajaxtools.com • info@ajaxtools.com



Drill Rods "H" Thread



Length	"H" Thread 7/8" x 3-1/4" Shank Part No.	"H" Thread 7/8" x 4-1/4" Shank Part No.	"H" Thread 1" x 4-1/4" Shank Part No.
	12"	64010	64210
18"	64020	64220	64420
24"	64030	64230	64430
30"	64040	64240	64440
36"	64050	64250	64450
48"	64060	64260	64460
60"	64070	64270	64470
72"	64080	64280	64480
96"	64090	64290	64490
120"	64100	64300	64500

Maximus Carbide "H" Threaded Rock Bits



Part No.	Hole Dia.	Pilot Dia.	Carbide Ht.
63600	1-3/8"	5/8"	11.5 mm
63601	1-1/2"	5/8"	11.5 mm
63602	1-5/8"	5/8"	11.5 mm
63603	1-3/4"	5/8"	11.5 mm
63604	1-7/8"	5/8"	11.5 mm
63605	2"	1-1/8"	11.5 mm
63606	2-1/4"	1-1/8"	11.5 mm
63607	2-1/2"	1-1/8"	11.5 mm
63608	2-3/4"	1-1/8"	11.5 mm
63609	3"	1-1/8"	11.5 mm

"H" Extension Rods



Part No.	Description	Length
64710	"H" Extention Rod	12"
64720	"H" Extention Rod	18"
64730	"H" Extention Rod	24"
64740	"H" Extention Rod	30"
64750	"H" Extention Rod	36"
64760	"H" Extention Rod	48"
64770	"H" Extention Rod	60"
64780	"H" Extention Rod	72"
64790	"H" Extention Rod	96"
64800	"H" Extention Rod	120"



"H" THREADED DRILL ROD ASSEMBLY WITH MAXIMUS CARBIDE BIT

"H" Thread Female Coupler



Part No.	Description
64700	"H" Thread Female Coupler



Ajax Tool Works, Inc.

10801 Franklin Ave. Franklin Park, IL 60131 • toll free: 800-323-9129 toll free fax: 800-424-2529
www.ajaxtools.com • info@ajaxtools.com